

FLH Glide Bike Fairing Insert with USB Charger

Installation and care for USB Charging Unit

FLH Glide Bike Fairing Insert with USB Charger takes the place of the existing factory fairing plugs. The FLH Glide Bike Fairing Insert with USB Charger comes complete with USB charger and fairing mount

#1: Carefully remove FLH Glide Bike Fairing Insert with USB Charger from packaging.

#2 Remove the existing fairing plug or gauge from the motorcycle fairing. If there is wiring attached find the positive and negative lines and secure them for re-installation to new gauge. If your installing the gauge into a plug hole that has a blank plug you will need to find suitable positive and negative feed lines.

Installation tip from a valued customer: *"I did not have to remove the fairing at all. I wish all things were that easy to install. ;-)* Once I cut a 1/2" hole, put my finger in it and pulled, the factory plug came out and the new parts just snapped right into place!"

#3: Orient the fairing plug insert to the proper position that it will install into the motorcycle fairing. We used the two large key tabs and noted the one as bottom.

#3: Adjust the position of the USB device inside the fairing plug to the desired orientation (USB can be horizontal, vertical or other) then make sure the screw device on the back of the USB is secure and ready to install.

#4: Connect the positive and negative wiring to the marked terminals on the back side of the USB device.

(IMPORTANT: Correct wiring is critical. Positive to positive and negative to negative. Device damage or failure may occur if improperly connected.)



#5: After making sure the connections are secure mount plug into fairing by snapping plug into place.



Enjoy your Marlin's Product



Technical support: 248-683-1536
www.marlinlocks.com

Design, Materials, Specifications & Pricing Subject To Change Without Notice