


General Care, Installation and Operation Instructions



Set Time



Set Screw

IMPORTANT - READ THIS FIRST!
RETURNS MUST BE PACKED TO ELIMINATE DAMAGE
DAMAGED RETURNS WILL NOT BE ACCEPTED

DO NOT push on the glass face for any reason. Push on the chrome ring or bezel to install.

The mount can be polished and cared for with a quality chrome polish.

Your new clock is waterproof, shock resistant and the numbers will glow in the dark for a limited time. *The face must be exposed to a light source before you ride to charge and activate the glow in the dark feature.*

The BPC Handlebar Clock fits on 1" bars or 7/8" bars utilizing a not included extended set screw.

The BPC Handlebar Clock comes with one set screw for clock retention on 1" bars.

1) Carefully remove the item from its package.

2) To install the clock place it over the handlebars in a location that the unit fits comfortably and will fit tightly against the back of the bars.

3) Tighten the set screw against the bars until the plastic tip of the set screw is sufficiently compressed and the unit is secured to the bars.

Note: You may use a dab of blue lock tight on the set screw to stop it from becoming loose.

SETTING THE TIME: The crown to adjust the time is located on the bottom of the clock housing at the 6 o'clock position. To set the time, carefully pull the crown out and turn it until the desired time is show. Push crown back in to the normal position to restart clock.

BATTERY REPLACEMENT: CAUTION: DO NOT LIFT THE MOVEMENT OUT OF THE CASE

When the clock loses time or stops the battery is due for replacement. The battery is accessible from the backside of the clock. Our clocks are manufactured with a screw on/off back cover. You may buy a back removal tool from us or use a needle nose pliers to easily remove and replace the back cover. A jeweler or watch band shop will also have a tool to remove the backing of the clock. The battery is retained in position by a tiny metal plate. Move the plate sideways to remove battery. Be sure when replacing the battery to use the same number or equivalent button cell (#377), with positive pole (+) facing outward. Make sure that it is retained securely in position by the metal plate. Replace cover making sure the O ring is properly in position and will form a satisfactory seal.

Your Clock will not require you to open it prior to a battery replacement. No other serviceable parts.

RETURNS MUST BE PACKED TO ELIMINATE DAMAGE

DAMAGED ITEMS WILL NOT BE ACCEPTED

If returning an item after obtaining an authorization number please send it to:

Big Paul's Cycle 5139 Juniper Dr. Commerce Twp., MI 48382

Make sure you return items using a trackable service method with adequate insurance.

Big Paul's can not be responsible for lost or damaged returns.

Technical support: 248-408-2075 www.bigpaulscycle.com