



Enjoy your Marlin's Product

Marlin's Liquid Filled Oil Pressure Gauge

Installation, Care and Use of Liquid Filled Oil Pressure Gauge

LIQUID-FILLED OIL PRESSURE GAUGE KIT

Easy to install. Helps you spot problems early, before a warning light indicates a problem.

- Marlin's 1/8 NPT rear mount liquid filled oil pressure gauges are available in 0-100 PSI in white face or black face.
- Allows monitoring of oil pressure while riding. Reduces costly engine repairs and downtime.
- Won't interfere with warning light function.
- Large, clear numbers for faster, easier reading.
- Gauge face is 1 3/8".

IMPORTANT

- Gauge and face are filled with liquid glycerin to dampen "soften" vibration and reduce needle fluctuations (also extends gauge life).
- Air bubble in face in NORMAL and needs to be there for gauge to work properly. (liquid may be replaced if loss occurs, use only Marlin approved glycerin - do not overfill, leave a bubble about the size of a nickel).
- Gauge is calibrated 0 to 100 by tens in 2-lb. increments.
- For plastic lens clean with a good car wax or plastic cleaner. For glass lens clean with a good glass cleaner.
- Use Teflon tape on all threads, careful not to cover hole used for pressure reading.
- Use wrench at base of unit to tighten - gently as needed - do not hold by gauge to tighten.
- Start motor and check for leaks.

These premium quality gauges fit our rocker box head temperature kits used on Twin Cam and Evolution style motors.

Please call or visit our web site for details

- Rubber fill plug is replaceable if needed.



Please contact Marlin's for service before returning item to dealer.

***Technical support: 248-683-1536
www.marlinsclocks.com***